

1 1/2" MAX DOW STYROFOAM™
 SPRAY POLYURETHANE FOAM
 CM SERIES IN ALL STUD CAVITIES

DOW THERMAX™ cl
 EXTERIOR INSULATION
 5/8"-2" THICK
 (HORIZONTAL SHIPLAPPED
 BOARDJOINT ON THICKNESSES
 >/= 1.55" THICK)

DOW WEATHERMATE™
 STRAIGHT FLASHING
 AT ALL THERMAX JOINTS

THREE COAT STUCCO
 AND LATH ON
 BUILDING PAPER
 BOND BREAK

DOW THERMAX™ cl
 EXTERIOR INSULATION
 5/8"-2" THICK
 (HORIZONTAL SHIPLAPPED
 BOARDJOINT ON THICKNESSES
 >/= 1.55" THICK)

OPTIONAL DEFLECTION JOINT
 DOW WEATHERMATE™ FLASHING
 BUILDING PAPER BOND BREAK
 BEHIND STUCCO J-BEAD

STEEL STUD
 MIN 20 GAUGE, MAX 24"OC,
 LATERAL BRACING EVERY
 4'-0" VERTICALLY

5/8" TYPE X GYPSUM SHEATHING

STEEL STUD
 MIN 20 GAUGE, MAX 24"OC,
 LATERAL BRACING EVERY
 4'-0" VERTICALLY

CONCRETE SLAB


METAL DECK

METAL CLOSURE
 ANGLE

DEFLECTION TRACK

AIR CAVITY
 FACE BRICK

7/8" VARIES MIN 3-5/8"



DETAIL AT FLOOR SLAB

REFERENCE DETAIL: REGISTERED PROFESSIONAL TO REVIEW PRIOR TO USE

<p>DETAIL</p>	<p>TITLE: WALL: THREE COAT STUCCO – THERMAX™ WALL SYSTEM</p>	<p>SKETCH NUMBER</p>
<p>The Dow Chemical Company Dow Building Solutions</p>	<p>Date: 05/15/2009 Scale: 1-1/2"=1'-0" Drawn: ---</p>	<p>SK-S3 3 OF 7</p>