

1 1/2" MAX **DOW STYROFOAM™**  
**SPRAY POLYURETHANE FOAM**  
**CM SERIES** IN ALL STUD CAVITIES

**DOW THERMAX™ cl**  
**EXTERIOR INSULATION**  
 5/8"-2" THICK  
 (HORIZONTAL SHIPLAPPED  
 BOARD JOINT ON THICKNESSES  
 >/= 1.55" THICK)

**DOW WEATHERMATE™**  
**STRAIGHT FLASHING**  
 AT ALL THERMAX JOINTS

THREE COAT STUCCO  
 AND LATH ON  
 BUILDING PAPER  
 BOND BREAK

BUILDING PAPER BOND BREAK  
 LAPPED OVER TOP OF  
 STUCCO WEEP SCREED

WRAP BOTTOM EDGE OF  
**DOW THERMAX™ cl**  
**EXTERIOR INSULATION**  
 WITH AN INSECT SCREEN

7"  
 8" VARIES MIN 3-5/8"

5/8" TYPE X GYPSUM SHEATHING

STEEL STUD  
 MIN 20 GAUGE, MAX 24" OC,  
 LATERAL BRACING EVERY  
 4'-0" VERTICALLY


CAPILLARY BREAK MEMBRANE

CONCRETE SLAB

VAPOR BARRIER

**DOW STYROFOAM™**

FOUNDATION WALL



## DETAIL: BASE FLASHING AT FOUNDATION

REFERENCE DETAIL: REGISTERED PROFESSIONAL TO REVIEW PRIOR TO USE

DETAIL

TITLE: WALL: THREE COAT STUCCO -  
 THERMAX™ WALL SYSTEM

SKETCH NUMBER

SK-S7

The Dow Chemical Company  
 Dow Building Solutions

Date: 05/15/2009  
 Scale: 1-1/2"=1'-0"  
 Drawn: ---

7 OF 7